

RVV

Gauge	Number of Conductors	Stranding	Insulation Thickness (mm)	Insulation Thickness (inches)	Jacket Thickness (mm)	Jacket Thickness (inches)	Nominal Diameter (mm)	Nominal Diameter (inches)	Weight Per 1000ft
0.750	2	24/0.20	0.600	0.024	0.800	0.031	6.400	0.252	0.000
0.750	3	24/0.20	0.600	0.024	0.800	0.031	6.800	0.268	0.000
0.750	4	24/0.20	0.600	0.024	0.800	0.031	7.400	0.291	0.000
0.750	5	24/0.20	0.600	0.024	0.900	0.035	8.400	0.331	0.000
1.000	2	32/0.20	0.600	0.024	0.800	0.031	6.700	0.264	0.000
1.000	3	32/0.20	0.600	0.024	0.800	0.031	7.200	0.284	0.000
1.000	4	32/0.20	0.600	0.024	0.900	0.035	8.000	0.315	0.000
1.000	5	32/0.20	0.600	0.024	0.900	0.035	8.900	0.351	0.000
1.500	2	30/0.25	0.700	0.028	0.800	0.031	7.700	0.303	0.000
1.500	3	30/0.25	0.700	0.028	0.900	0.035	8.500	0.335	0.000
1.500	4	30/0.25	0.700	0.028	1.000	0.039	9.400	0.370	0.000
1.500	5	30/0.25	0.700	0.028	1.100	0.043	10.600	0.417	0.000
2.500	2	49/0.25	0.800	0.031	1.000	0.039	9.400	0.370	0.000
2.500	3	49/0.25	0.800	0.031	1.100	0.043	10.200	0.402	0.000
2.500	4	49/0.25	0.800	0.031	1.100	0.043	11.000	0.433	0.000
2.500	5	49/0.25	0.800	0.031	1.200	0.047	12.400	0.488	0.000